



SHAPELINE PRODUCT OVERVIEW

www.hella.com/shapeline

SHAPELINE
DESIGN YOUR LIGHT

CONTENT

Introduction	02
Configuration tool	03
Module overview	04 – 13
Application examples	14 – 17
Technical information	18 – 32
Connector overview	33
Mounting instructions	34



CUSTOMISED LIGHT DESIGN!

The variety and range of shapes and various combination options paired with a technically optimised product design make the new Shapeline light series a true innovation in vehicle lighting.

Whether the front, side or rear of a vehicle, every vehicle series - whether big or small - can have a unique and, above all, consistent look using a customised configuration and arrangement of lamps. This allows us to meet the demands of vehicle manufacturers with lower numbers of manufactured vehicles.

Along with innovative technology and the familiar high quality of HELLA's products, the variety of shapes of Shapeline lamps provide you with nearly infinite design freedom.

Design your light – with HELLA Shapeline!



Premium Design



Flexible



Robust



Simple and safe



ECE and SAE



Multivolt

DESIGN FREEDOM AT THE CLICK OF A MOUSE

The HELLA Shapeline online configuration tool turns you into a lighting designer: With a few clicks, make your own vehicle light design for the front, sides, and rear – and see the result directly after, as applied convincingly to a car outline.

www.hella.com/shapeline



MODULE OVERVIEW

The modular HELLA Shapeline product range provides a variety of different light functions that can be combined with each other individually. Here, all lamps are available in two different designs: The classic straight-line **Shapeline Tech** design and the dynamic curved **Shapeline Style design**.

Tech or Style: The HELLA Shapeline series provides design freedom for nearly any application and vehicle, and achieves a consistent light signature for your vehicle at the same time.



FRONT

STYLE




Position lamps

Technical data see page 19.



Technical drawings




Reflex reflectors

Technical data see page 21.



Technical drawing



TECH




Position lamps

Technical data see page 19.



Technical drawing




Reflex reflectors

Technical data see page 21.



Technical drawing



FRONT

STYLE




Direction indicators

Technical data see page 20 – 21.



Technical drawings




Daytime running lamps and position lamps

Technical data see page 21.



Technical drawing



TECH




Direction indicators

Technical data see page 20.



Technical drawings



SIDE

STYLE




Direction indicators

Technical data see page 25.



Technical drawings




Reflex reflectors

Technical data see page 25.



Technical drawing



TECH




Direction indicators

Technical data see page 25.



Technical drawings




Reflex reflectors

Technical data see page 25.



Technical drawing



Clearance lamps

Technical data see page 21.



SIDE

STYLE



Side marker lamps

Technical data see page 24 – 25.



Technical drawing



TECH



Side marker lamps

Technical data see page 22 – 23.



Technical drawing

REAR

STYLE




Position lamps

Technical data see page 26.



Technical drawing




Tail-stop lamps

Technical data see page 26 – 27.



Technical drawings



TECH




Position lamps

Technical data see page 26.




Technical drawing




Tail-stop lamps

Technical data see page 26.



Technical drawing



REAR

STYLE




Direction indicators

Technical data see page 28 – 29.



Technical drawings



TECH




Direction indicators

Technical data see page 27.



Technical drawing



REAR

STYLE




Tail-stop-direction indicator lamps

Technical data see page 27.



Technical drawing




Reverse lamps

Technical data see page 30.



Technical drawings



TECH




Tail-stop-direction indicator lamps

Technical data see page 27.



Technical drawing




Reverse lamps

Technical data see page 29.




Technical drawing



REAR

STYLE




Rear fog lamps

Technical data see page 31 – 32.



Technical drawings



TECH




Rear fog lamps

Technical data see page 30 – 31.



Technical drawing



REAR

STYLE




Reflex reflectors

Technical data see page 32.



Technical drawings




Warning lamps

Technical data see page 32.



Technical drawings



TECH




Reflex reflectors

Technical data see page 32.



Technical drawing



APPLICATION EXAMPLES

The HELLA Shapeline series allows vehicle manufacturers specialising in various fields of application to give their vehicle series a distinctive yet at the same time consistent look and feel by means of individualised lamp constellations.

On the following pages you will see examples of selected applications for a variety of target groups - ranging from agricultural vehicles through buses and caravans right up to trucks. These examples illustrate very clearly the wealth of possibilities opened up to you by Shapeline.

Whether it's **Shapeline Tech Design** or **Shapeline Style Design**: every design line offers countless combination options, which enable creativity to run wild and free. Grab yourself some inspiration!



CONSTRUCTION VEHICLES



MUNICIPAL VEHICLES



TRUCKS



MOTORHOMES





BUSES



E-CARS



EMERGENCY VEHICLES



AGRICULTURAL VEHICLES



FORKLIFTS



TRAILER



MOTORHOMES



APPLICATION EXAMPLES




SHAPELINE PRODUCTS ON THE VEHICLE

					
Style	Style	Style	Style	Style	Style
2BA 013 333-051	2BA 013 333-061	2SB 013 399-011	2SB 013 399-021	2ZR 013 401-051	2ZR 013 401-061
4 x	4 x	4 x	4 x	3 x	3 x
					
Style	Style	Style	Style		
2BM 013 339-031	2BM 013 339-041	2NE 013 343-051	2NE 013 343-061		
1 x	1 x	1 x	1 x		



SHAPELINE PRODUCTS ON THE VEHICLE

			
Style	Style	Style	Style
2SB 013 399-011	2SB 013 399-021	2BA 013 332-071	2BA 013 332-081
1 x	1 x	1 x	1 x
			
Style	Style	Style	Style
2ZR 013 401-111	2ZR 013 401-121	2NE 013 343-111	2NE 013 343-121
1 x	1 x	1 x	1 x



SHAPELINE PRODUCTS ON THE VEHICLE

			
Style	Style	Style	Style
2SB 013 399-011	2SB 013 399-021	2BA 013 332-011	2BA 013 332-021
1 x	1 x	1 x	1 x
			
Style	Style		
8RA 013 347-051	8RA 013 347-061		
1 x	1 x		

TECHNICAL INFORMATION

From the connection type to energy consumption and voltage: On the following pages, you will find the most important detail information and technical data clearly structured in table form for each module.



Electromagnetic compatibility EMC 5

Electromagnetic compatibility (EMC) tested and EU type approval issued.



ADR/GGVS certification for transport of dangerous goods

Lamp approved for transport of dangerous goods according to the European Agreement for the International Carriage of Dangerous Goods by Road (ADR; in German, GGVS).



Voltage range 9 – 32 V

Defines the power supply of the lamp.



Short-circuit protection integrated

Protected against short circuit by means of an amp fuse.



ECE type approval

Product is licensed according to ECE guidelines.



SAE type approval

Product has SAE type approval.



Protection class IP X9K

Resistant to high-pressure cleaning



AECQ – components qualified in accordance with the automotive standard

Components qualified according to automotive standard.



Operating temperature - 40 C – + 60 C

Thermal management and an optimised housing design guarantee full functionality for all operating temperatures through product tests from -40°C to +60°C.



Indicator failure check ISO 13207

Regulation in accordance with ECE-R48: The driver must be informed if the indicator function fails. To remain legally compliant, this requirement must also be fulfilled for LED lamps. This requirement is fulfilled by means of an integrated self-diagnostic unit on the PCB of the LED and an electrical pulse. Since the end of 2011, this HELLA failure check with a pulse has been an ISO Standard: ISO 13207.



Protection class IP 6K7

International Protection (IP) in accordance with DIN 40060 part 9. The higher the protective class, the better the protection against penetrating media. IP 67 maximum value
→ Completely sealed against dust and water.



Polarity reversal protection included

Even if the connecting cable is connected the wrong way round, there is still no danger for the electronics.

											
	Position lamp front	Position lamp front LH	Position lamp front RH	Position lamp Wing front LH hor.	Position lamp Wing front RH hor.	Position lamp Wing front LH vert.	Position lamp Wing front RH vert.	Position lamp Slim front LH hor.	Position lamp Slim front RH hor.	Position lamp Slim front LH vert.	Position lamp Slim front RH vert.
Design	Tech	Style	Style	Style	Style	Style	Style	Style	Style	Style	Style
Homologation	ECE/SAE	ECE/SAE	ECE/SAE	ECE/SAE	ECE/SAE	ECE/SAE	ECE/SAE	ECE/SAE	ECE/SAE	ECE/SAE	ECE/SAE
Connectors and wiring	6.3 mm receptacles 2100 mm	Open ends 250 mm	Open ends 5000 mm	AMP SS 250 mm	Open ends 250 mm	Amphenol 250 mm	AMP SS 250 mm	Open ends 250 mm	Amphenol 250 mm	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS
Device number (Please add packaging index as the last number -1 Individual packaging or -7 Multiple-item packaging)	2PF 013 323-21	2PF 013 323-22	2PF 013 323-20	2PF 013 324-01	2PF 013 324-03	2PF 013 324-05	2PF 013 324-02	2PF 013 324-04	2PF 013 324-06	2PF 013 325-01	2PF 013 325-02
Minimum order quantity for packaging index 7	50	50	40	50	50	50	50	50	50	30	30
Voltage range: 9V – 16V	•	•	•	•	•	•	•	•	•	•	•
Voltage range: 18V – 32V	•	•	•	•	•	•	•	•	•	•	•
Nominal voltage [V]	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24
Current flow at 13.5V/28V [mA]	26 / 32	26 / 32	26 / 32	26 / 32	26 / 32	26 / 32	26 / 32	26 / 32	26 / 32	315 / 340	315 / 340
Number of LEDs	1	1	1	1	1	1	1	1	1	30	30
Power consumption at 13.5V/28V [W]	0.35 / 0.9	0.35 / 0.9	0.35 / 0.9	0.35 / 0.9	0.35 / 0.9	0.35 / 0.9	0.35 / 0.9	0.35 / 0.9	0.35 / 0.9	max. 5.5	max. 5.5
Dimensions (length / width / height in mm)	62/40/18	62/40/18	62/40/18	138.6/40/20	138.6/40/20	138.6/40/20	138.6/40/20	138.6/40/20	138.6/40/20	389.1/104/25	389.1/104/25
Operating temp.: -40 – +60°C	•	•	•	•	•	•	•	•	•	•	•
Mounting system (1= tape; 2= screw; 3= snap-ball-head bolt)*	1*	1*	1*	1*	1*	1*	1*	1*	1*	2*	2*
Mounting tolerance (+/- angle [°])	0	0	0	6	6	6	6	6	6	6	6
HELLA specification HN67101 class 6.3 + 7.2	•	•	•	•	•	•	•	•	•	•	•
Polarity reversal protection	•	•	•	•	•	•	•	•	•	•	•
Failure protection: current detection, 1 LED off = all off	•	•	•	•	•	•	•	•	•	•	•
Failure protection ISO13207	•	•	•	•	•	•	•	•	•	•	•
Integrated short-circuit protection	•	•	•	•	•	•	•	•	•	•	•

* Other fastening options available upon request

											
	Direction indicator Wing front LH hor.	Direction indicator Wing front RH hor.	Direction indicator Wing front LH hor. Wiping L→R	Direction indicator Wing front RH hor. Wiping R→L	Direction indicator Wing front RH hor. Wiping R→L	Direction indicator Wing front LH hor. Wiping L→R	Direction indicator Wing front LH vert.	Direction indicator Wing front RH vert.	Direction indicator front	Direction indicator front	Direction indicator wiping front
Design	Style	Style	Style	Style	Style	Style	Style	Style	Tech	Tech	Tech
Homologation	ECE/SAE	ECE/SAE	ECE	ECE	ECE	ECE	ECE/SAE	ECE/SAE	ECE/SAE > 2032	ECE / SAE < 2032	ECE
Connectors and wiring	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP	Integrated 2-pin AMP
Device number (Please add packaging index as the last number -1 Individual packaging or -7 Multiple-item packaging)	2BA 013 334-01	2BA 013 334-02	2BA 013 334-05	2BA 013 334-06	2BA 013 334-08	2BA 013 334-07	2BA 013 334-03	2BA 013 334-04	2BA 013 330-01	2BA 013 398-00	2BA 013 398-01
Minimum order quantity for packaging index 7	30	30	30	30	30	30	30	30	35	140	140
Voltage range: 9V – 16V	•	•	•	•	•	•	•	•	•	•	•
Voltage range: 18V – 32V	•	•	•	•	•	•	•	•	•	•	•
Nominal voltage [V]	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24
Current flow at 13.5V/28V [mA]	407 / 197	407 / 197	407 / 197	407 / 197	407 / 197	407 / 197	407 / 197	407 / 197	408 / 240	217 / 105	217 / 105
Number of LEDs	12	12	12	12	12	12	12	12	12	6	6
Power consumption at 13.5V/28V [W]	max. 5.5	max. 5.5	max. 5.5	max. 5.5	max. 5.5	max. 5.5	max. 5.5	max. 5.5	5.5 / 6.7	max. 2.93	max. 2.93
Dimensions (length / width / height in mm)	389.1/104/25	389.1/104/25	389.1/104/25	389.1/104/25	389.1/104/25	389.1/104/25	389.1/104/25	389.1/104/25	149.1/104/25	128/40/25	128/40/25
Operating temp.: -40 – +60°C	•	•	•	•	•	•	•	•	•	•	•
Mounting system (1= tape; 2= screw; 3= snap-ball-head bolt)*	2*	2*	2*	2*	2*	2*	2*	2*	2*	1*	1*
Mounting tolerance (+/- angle [°])	6	6	6	6	6	6	0	0	0	0	0
HELLA specification HN67101 class 6.3 + 7.2	•	•	•	•	•	•	•	•	•	•	•
Polarity reversal protection	•	•	•	•	•	•	•	•	•	•	•
Failure protection: current detection, 1 LED off = all off											
Failure protection ISO13207	•	•	•	•	•	•	•	•	•	•	•
Integrated short-circuit protection	•	•	•	•	•	•	•	•	•	•	•

* Other fastening options available upon request

Note: The Shapeline direction indicators (for front and rear), tail-stop lamps and tail-stop-direction indicator lamps are not approved for the vehicle class M1 with < 3.5 t.

														
Direction indicator Slim front LH hor.	Direction indicator Slim front RH hor.	Direction indicator Slim front LH hor. Wiping L→R	Direction indicator Slim front RH hor. Wiping R→L	Direction indicator Slim front LH vert.	Direction indicator Slim front RH vert.	Daytime running and position lamp Slim front LH	Daytime running and position lamp Slim front RH	Reflex reflector front	Reflex reflector front LH	Reflex reflector front RH	Clearance lamp side mounting Light irradiation to the front and back	Clearance lamp side mounting Light irradiation to the front and back		
Style	Style	Style	Style	Style	Style	Style	Style	Tech	Style	Style	Tech	Tech		
ECE/SAE<2032	ECE/SAE<2032	ECE	ECE	ECE/SAE<2032	ECE/SAE<2032	ECE/SAE	ECE/SAE	ECE/SAE	ECE/SAE	ECE/SAE	ECE	SAE		
Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 3-pin AMP SS	Integrated 3-pin AMP SS	•	•	•	open ends 500 mm	Integrated 2-pin AMP		
2BA 013 335-03	2BA 013 335-04	2BA 013 335-01	2BA 013 335-02	2BA 013 335-05	2BA 013 335-06	2PT 014 627-01	2PT 014 627-02	8RA 013 403-01	8RA 013 347-01	8RA 013 347-02	2XS 013 327-01	2XS 013 327-00	2XS 013 327-03	2XS 013 327-02
84	84	84	84	84	84			299	240	240	50	50	50	50
•	•	•	•	•	•	•	•				•	•	•	•
12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24				12/24	12/24	12/24	12/24
217 / 105	217 / 105	217 / 105	217 / 105	217 / 105	217 / 105	DRL: 300/158 PO: 32/26	DRL: 300/158 PO: 32/26				50/25	50/25	60/30	60/30
6	6	6	6	6	6	6	6							
max. 2.93	max. 2.93	max. 2.93	max. 2.93	max. 2.93	max. 2.93	DRL: 4.05/4.424 PO: 0.43/0.728	DRL: 4.05/4.424 PO: 0.43/0.728				0.68/0.70	0.68/0.70	0.81/0.84	0.81/0.84
199.8/40/25	199.8/40/25	199.8/40/25	199.8/40/25	199.8/40/25	199.8/40/25	199.8/40/25	199.8/40/25	113/40/12	163.5/40/12	163.5/40/12	91/40.5/21	91/40.5/21	91/40.5/21	91/40.5/21
•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
1*	1*	1*	1*	1*	1*	2	2	1	1	1	1*	1*	1*	1*
6	6	6	6	0	0	0	0	0	6	6	0	0	0	0
•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•				•	•	•	•

DRL = Daytime running light, PO = Position light

Note: The Shapeline direction indicators (for front and rear), tail-stop lamps and tail-stop-direction indicator lamps are not approved for the vehicle class M1 with < 3.5 t.

Design	Tech							Tech							Tech	Tech	Tech							Tech											
Homologation	ECE SM1/SAE							ECE SM1/SAE							ECE SM2	ECE SM2	ECE SM1/SAE							ECE SM1/SAE											
Connectors and wiring	       							       							     							  							 						
Device number (Please add packaging index as the last number -1 Individual packaging or -7 Multiple-item packaging)	2PS 013 300-01	2PS 013 300-02	2PS 013 300-03	2PS 013 300-04	2PS 013 300-05	2PS 013 300-06	2PS 013 300-07	2PS 013 301-01	2PS 013 301-02	2PS 013 301-03	2PS 013 301-04	2PS 013 301-05	2PS 013 301-06	2PS 013 301-07	2PS 013 302-01	2PS 013 302-02	2PS 013 302-00	2PS 013 302-11	2PS 013 302-12	2PS 013 302-10	2PS 013 300-25	2PS 013 300-26	2PS 013 300-27	2PS 013 300-28	2PS 013 300-29	2PS 013 300-24	2PS 013 300-30	2PS 013 300-31	2PS 013 301-25	2PS 013 301-26	2PS 013 301-27				
Minimum order quantity for packaging index 7	50	100	50	50	50	100	100	50	100	50	50	50	100	100	120	120	120	120	120	120	50	100	50	50	50	100	50	100	100	50	100	50			
Voltage range: 9V – 16V	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•				
Voltage range: 18V – 32V	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•				
Nominal voltage [V]	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12	12	12	12	12	12	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24				
Current flow at 13.5V/28V [mA]	41 / 47	41 / 47	41 / 47	41 / 47	41 / 47	41 / 47	41 / 47	41 / 47	41 / 47	41 / 47	41 / 47	41 / 47	41 / 47	41 / 47	38 / -	38 / -	38 / -	38 / -	38 / -	38 / -	41 / 47	41 / 47	41 / 47	41 / 47	41 / 47	41 / 47	41 / 47	41 / 47	41 / 47	41 / 47	41 / 47				
Number of LEDs	3	3	3	3	3	3	3	3	3	3	3	3	3	3	1	1	1	1	1	1	3	3	3	3	3	3	3	3	3	3	3				
Power consumption at 13.5V/28V [W]	0.55 / 1.3	0.55 / 1.3	0.55 / 1.3	0.55 / 1.3	0.55 / 1.3	0.55 / 1.3	0.55 / 1.3	0.55 / 1.3	0.55 / 1.3	0.55 / 1.3	0.55 / 1.3	0.55 / 1.3	0.55 / 1.3	0.55 / 1.3	0.5	0.5	0.5	0.5	0.5	0.5	0.55 / 1.3	0.55 / 1.3	0.55 / 1.3	0.55 / 1.3	0.55 / 1.3	0.55 / 1.3	0.55 / 1.3	0.55 / 1.3	0.55 / 1.3	0.55 / 1.3	0.55 / 1.3				
Dimensions (length / width / height in mm)	168/34/15.5	168/34/15.5	168/34/15.5	168/34/15.5	168/34/15.5	168/34/15.5	168/34/15.5	168/34/15.5	168/34/15.5	168/34/15.5	168/34/15.5	168/34/15.5	168/34/15.5	168/34/15.5	168/34/15.5	168/34/15.5	168/34/15.5	168/34/15.5	168/34/15.5	168/34/15.5	171.8/37.8/17.1	171.8/37.8/17.1	171.8/37.8/17.1	171.8/37.8/17.1	171.8/37.8/17.1	171.8/37.8/17.1	171.8/37.8/17.1	171.8/37.8/17.1	171.8/37.8/17.1	171.8/37.8/17.1	171.8/37.8/17.1				
Operating temp.: -40 – +60°C	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•			
Mounting system (1= tape; 2= screw; 3= snap-ball-head bolt)*	1*	1*	1*	1*	1*	1*	1*	1*	1*	1*	1*	1*	1*	1*	1*	1*	1*	1*	1*	1*	2*	2*	2*	2*	2*	2*	2*	2*	2*	2*	2*				
Mounting tolerance (+/- angle [°])	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0				
HELLA specification HN67101 class 6.3 + 7.2	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•			
Polarity reversal protection	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•			
Failure protection: current detection, 1 LED off = all off	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•			
Failure protection ISO13207	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•			
Integrated short-circuit protection	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•			

* Other fastening options available upon request



Side marker lamp with reflex reflector amber vert. rubber housing																
Tech																
ECE SM1/SAE																
	•	•	•	0	2*	•	171.8/37.8/17.1	055 / 1.3	3	41 / 47	12/24	•	•	50	2PS 013 301-28	QL 1300mm
	•	•	•	•	•	•	171.8/37.8/17.1	055 / 1.3	3	41 / 47	12/24	•	•	50	2PS 013 301-29	6.3 mm receptacles 2100 mm
	•	•	•	•	•	•	171.8/37.8/17.1	055 / 1.3	3	41 / 47	12/24	•	•	100	2PS 013 301-24	open ends 500 mm
	•	•	•	•	•	•	171.8/37.8/17.1	055 / 1.3	3	41 / 47	12/24	•	•	50	2PS 013 301-30	Open ends 1500 mm
	•	•	•	•	•	•	171.8/37.8/17.1	055 / 1.3	3	41 / 47	12/24	•	•	100	2PS 013 301-31	Amphenol 500 mm
	•	•	•	•	•	•	168/34/15.5	055 / 1.3	3	41 / 47	12/24	•	•	50	2PS 013 303-01	EC angled 1000 mm
	•	•	•	•	•	•	168/34/15.5	055 / 1.3	3	41 / 47	12/24	•	•	100	2PS 013 303-02	AMP SS 450 mm
	•	•	•	•	•	•	168/34/15.5	055 / 1.3	3	41 / 47	12/24	•	•	50	2PS 013 303-03	EC straight 1300 mm
	•	•	•	•	•	•	168/34/15.5	055 / 1.3	3	41 / 47	12/24	•	•	50	2PS 013 303-04	QL 1300 mm
	•	•	•	•	•	•	168/34/15.5	055 / 1.3	3	41 / 47	12/24	•	•	50	2PS 013 303-05	6.3 mm receptacles 2100 mm
	•	•	•	•	•	•	168/34/15.5	055 / 1.3	3	41 / 47	12/24	•	•	100	2PS 013 303-00	open ends 500 mm
	•	•	•	•	•	•	168/34/15.5	055 / 1.3	3	41 / 47	12/24	•	•	50	2PS 013 303-06	Open ends 1500 mm
	•	•	•	•	•	•	168/34/15.5	055 / 1.3	3	41 / 47	12/24	•	•	100	2PS 013 303-07	Amphenol 500 mm
	•	•	•	•	•	•	168/34/15.5	055 / 1.3	3	41 / 47	12/24	•	•	50	2PS 013 304-01	EC angled 1000 mm
	•	•	•	•	•	•	168/34/15.5	055 / 1.3	3	41 / 47	12/24	•	•	100	2PS 013 304-02	AMP SS 450 mm
	•	•	•	•	•	•	168/34/15.5	055 / 1.3	3	41 / 47	12/24	•	•	50	2PS 013 304-03	EC straight 1300 mm
	•	•	•	•	•	•	168/34/15.5	055 / 1.3	3	41 / 47	12/24	•	•	50	2PS 01 3304-04	QL 1300 mm
•	•	•	•	•	•	168/34/15.5	055 / 1.3	3	41 / 47	12/24	•	•	50	2PS 013 304-05	6.3 mm receptacles 2100 mm	
•	•	•	•	•	•	168/34/15.5	055 / 1.3	3	41 / 47	12/24	•	•	100	2PS 013 304-00	open ends 500 mm	
•	•	•	•	•	•	168/34/15.5	055 / 1.3	3	41 / 47	12/24	•	•	50	2PS 013 304-06	Open ends 1500 mm	
•	•	•	•	•	•	168/34/15.5	055 / 1.3	3	41 / 47	12/24	•	•	100	2PS 013 304-07	Amphenol 500 mm	
•	•	•	•	•	•	171.8/37.8/17.1	055 / 1.3	3	41 / 47	12/24	•	•	50	2PS 013 303-25	EC angled 1000 mm	
•	•	•	•	•	•	171.8/37.8/17.1	055 / 1.3	3	41 / 47	12/24	•	•	100	2PS 013 303-26	AMP SS 450 mm	
•	•	•	•	•	•	171.8/37.8/17.1	055 / 1.3	3	41 / 47	12/24	•	•	50	2PS 013 303-27	EC straight 1300 mm	
•	•	•	•	•	•	171.8/37.8/17.1	055 / 1.3	3	41 / 47	12/24	•	•	50	2PS 013 303-28	QL 1300 mm	
•	•	•	•	•	•	171.8/37.8/17.1	055 / 1.3	3	41 / 47	12/24	•	•	50	2PS 013 303-29	6.3 mm receptacles 2100 mm	
•	•	•	•	•	•	171.8/37.8/17.1	055 / 1.3	3	41 / 47	12/24	•	•	100	2PS 013 303-24	open ends 500 mm	
•	•	•	•	•	•	171.8/37.8/17.1	055 / 1.3	3	41 / 47	12/24	•	•	50	2PS 013 303-30	Open ends 1500 mm	
•	•	•	•	•	•	171.8/37.8/17.1	055 / 1.3	3	41 / 47	12/24	•	•	100	2PS 013 303-31	Amphenol 500 mm	
•	•	•	•	•	•	171.8/37.8/17.1	055 / 1.3	3	41 / 47	12/24	•	•	50	2PS 013 304-25	EC angled 1000 mm	
•	•	•	•	•	•	171.8/37.8/17.1	055 / 1.3	3	41 / 47	12/24	•	•	100	2PS 013 304-26	AMP SS 450 mm	
•	•	•	•	•	•	171.8/37.8/17.1	055 / 1.3	3	41 / 47	12/24	•	•	50	2PS 013 304-27	EC straight 1300 mm	
•	•	•	•	•	•	171.8/37.8/17.1	055 / 1.3	3	41 / 47	12/24	•	•	50	2PS 013 304-28	QL 1300 mm	
•	•	•	•	•	•	171.8/37.8/17.1	055 / 1.3	3	41 / 47	12/24	•	•	50	2PS 013 304-29	6.3 mm receptacles 2100 mm	
•	•	•	•	•	•	171.8/37.8/17.1	055 / 1.3	3	41 / 47	12/24	•	•	100	2PS 013 304-24	open ends 500 mm	
•	•	•	•	•	•	171.8/37.8/17.1	055 / 1.3	3	41 / 47	12/24	•	•	50	2PS 013 304-30	Open ends 1500 mm	
•	•	•	•	•	•	171.8/37.8/17.1	055 / 1.3	3	41 / 47	12/24	•	•	100	2PS 013 304-31	Amphenol 500 mm	

								
	Side marker lamp amber LH	Side marker lamp amber RH	Side marker lamp amber LH	Side marker lamp amber RH	Side marker lamp amber LH rubber housing	Side marker lamp amber RH rubber housing	Side marker lamp red LH	Side marker lamp red RH
Design	Style	Style	Style	Style	Style	Style	Style	Style
Homologation	ECE SM1/SAE	ECE SM1/SAE	ECE SM2	ECE SM2	ECE SM1/SAE	ECE SM1/SAE	SAE	SAE
Connectors and wiring	AMP SS 250 mm, overmolded	6.3 mm receptacles 250 mm	Open ends 250 mm	Amphenol 500 mm	AMP SS 250 mm, overmolded	6.3 mm receptacles 250 mm	Open ends 250 mm	Amphenol 500 mm
Device number (Please add packaging index as the last number - 1 Individual packaging or - 7 Multiple-item packaging)	2PS 013 305-01	2PS 013 305-03	2PS 013 305-05	2PS 013 305-07	2PS 013 305-02	2PS 013 305-04	2PS 013 305-06	2PS 013 305-08
Minimum order quantity for packaging index 7	120	120	120	100	120	120	120	100
Voltage range: 9V – 16V	•	•	•	•	•	•	•	•
Voltage range: 18V – 32V	•	•	•	•	•	•	•	•
Nominal voltage [V]	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24
Current flow at 13.5V/28V [mA]	41 / 47	41 / 47	41 / 47	41 / 47	41 / 47	41 / 47	41 / 47	41 / 47
Number of LEDs	3	3	3	3	3	3	3	3
Power consumption at 13.5V/28V [W]	0.55 / 1.3	0.55 / 1.3	0.55 / 1.3	0.55 / 1.3	0.55 / 1.3	0.55 / 1.3	0.55 / 1.3	0.55 / 1.3
Dimensions (length / width / height in mm)	205/34/15.5	205/34/15.5	205/34/15.5	205/34/15.5	205/34/15.5	205/34/15.5	205/34/15.5	205/34/15.5
Operating temp.: -40 – +60°C	•	•	•	•	•	•	•	•
Mounting system (1= tape; 2= screw; 3= snap-ball-head bolt)*	1*	1*	1*	1*	1*	1*	1*	1*
Mounting tolerance (+/- angle [°])	0	0	0	0	0	0	0	0
HELLA specification HN67101 class 6.3 + 7.2	•	•	•	•	•	•	•	•
Polarity reversal protection	•	•	•	•	•	•	•	•
Failure protection: current detection, 1 LED off = all off	•	•	•	•	•	•	•	•
Failure protection ISO13207	•	•	•	•	•	•	•	•
Integrated short-circuit protection	•	•	•	•	•	•	•	•

* Other fastening options available upon request

[illegible]

SM1 (for all vehicle classes) = luminous intensity min. 4 cd, max. 25 cd
SM2 (only for M₁ classes) = luminous intensity min. 0.6 cd, max. 25 cd

																	
	Position lamp rear	Position lamp rear LH	Position lamp rear RH	Tail-stop lamp rear	Tail-stop lamp rear LH hor.	Tail-stop lamp rear RH hor.	Tail-stop lamp rear LH vert.	Tail-stop lamp rear RH vert.	Tail-stop lamp Wing rear LH hor.	Tail-stop lamp Wing rear RH hor.	Tail-stop lamp Wing rear LH vert.						
Design	Tech	Style	Style	Tech	Style	Style	Style	Style	Style	Style	Style						
Homologation	ECE/SAE	ECE/SAE	ECE/SAE	ECE/SAE	ECE/SAE	ECE/SAE	ECE/SAE	ECE/SAE	ECE/SAE	ECE/SAE	ECE/SAE						
Connectors and wiring	6.3 mm receptacles 2100 mm	Open ends 250 mm	Open ends 5000 mm	AMP SS 250 mm	Open ends 250 mm	Amphenol 250 mm	AMP SS 250 mm	Open ends 250 mm	Amphenol 250 mm	Integrated 3-pin AMP SS	Integrated 3-pin AMP SS						
Device number (Please add packaging index as the last number -1 Individual packaging or -7 Multiple-item packaging)	2SA 013 323-01	2SA 013 323-02	2SA 013 323-00	2SA 013 324-21	2SA 013 324-23	2SA 013 324-25	2SA 013 324-22	2SA 013 324-24	2SA 013 324-26	2SB 013 341-00	2SB 013 342-01	2SB 013 342-02	2SB 013 342-03	2SB 013 342-04	2SB 013 399-01	2SB 013 399-02	2SB 013 399-03
Minimum order quantity for packaging index 7	50	50	40	50	50	50	50	50	50	35	45	45	45	45	30	30	30
Voltage range: 9V – 16V	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Voltage range: 18V – 32V	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Nominal voltage [V]	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24
Current flow at 13.5V/28V [mA]	48 / 54	48 / 54	48 / 54	48 / 54	48 / 54	48 / 54	48 / 54	48 / 54	48 / 54	ST: 260 / 272 TL: 52 / 54	ST: 260 / 272 TL: 52 / 54	ST: 260 / 272 TL: 52 / 54	ST: 260 / 272 TL: 52 / 54	ST: 260 / 272 TL: 52 / 54	ST: 305 / 330 TL: 40 / 60	ST: 305 / 330 TL: 40 / 60	ST: 305 / 330 TL: 40 / 60
Number of LEDs	1	1	1	1	1	1	1	1	1	24 / 12	24 / 12	24 / 12	24 / 12	24 / 12	30	30	30
Power consumption at 13.5V/28V [W]	0.65 / 1.5	0.65 / 1.5	0.65 / 1.5	0.65 / 1.5	0.65 / 1.5	0.65 / 1.5	0.65 / 1.5	0.65 / 1.5	0.65 / 1.5	ST: 3.5 / 7.6 TL: 0.7 / 1.5	ST: 3.5 / 7.6 TL: 0.7 / 1.5	ST: 3.5 / 7.6 TL: 0.7 / 1.5	ST: 3.5 / 7.6 TL: 0.7 / 1.5	ST: 3.5 / 7.6 TL: 0.7 / 1.5	ST: 4.2 / 9.3 TL: 0.6 / 1.7	ST: 4.2 / 9.3 TL: 0.6 / 1.7	ST: 4.2 / 9.3 TL: 0.6 / 1.7
Dimensions (length / width / height in mm)	62/40/18	62/40/18	62/40/18	138.6/40/20	138.6/40/20	138.6/40/20	138.6/40/20	138.6/40/20	138.6/40/20	149.1/104/25	275.4/104/25	275.4/104/25	275.4/104/25	275.4/104/25	389.1/104/25	389.1/104/25	389.1/104/25
Operating temp.: -40 – +60°C	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Mounting system (1= tape; 2= screw; 3= snap-ball-head bolt)*	1*	1*	1*	1*	1*	1*	1*	1*	1*	2*	2*	2*	2*	2*	2*	2*	2*
Mounting tolerance (+/- angle [°])	0	0	0	6	6	6	6	6	6	0	0	0	0	0	6	6	0
HELLA specification HN67101 class 6.3 + 7.2	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Polarity reversal protection	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Failure protection: current detection, 1 LED off = all off	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Failure protection ISO13207	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Integrated short-circuit protection	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•

* Other fastening options available upon request

Note: The Shapeline direction indicators (for front and rear), tail-stop lamps and tail-stop-direction indicator lamps are not approved for the vehicle class M1 with < 3.5 t.

Tail-stop lamp Wing rear RH vert.	Tail-stop lamp Slim rear LH hor.	Tail-stop lamp Slim rear RH hor.	Tail-stop lamp Slim rear LH vert.	Tail-stop lamp Slim rear RH vert.	Tail-stop-direction indicator lamp rear	Tail-stop-direction indicator lamp rear LH hor.	Tail-stop-direction indicator lamp rear RH hor.	Tail-stop-direction indicator lamp rear LH vert.	Tail-stop-direction indicator lamp rear RH vert.	Direction indicator amber rear	Direction indicator clear rear
Style	Style	Style	Style	Style	Tech	Style	Style	Style	Style	Tech	Tech
ECE/SAE	ECE	ECE	ECE	ECE	ECE	ECE	ECE	ECE	ECE	ECE	ECE
ST: 4.2 / 9.3 TL: 0.6 / 1.7	B: 2 / 2.8 S: 0.3 / 0.8	B: 2 / 2.8 S: 0.3 / 0.8	B: 2 / 2.8 S: 0.3 / 0.8	B: 2 / 2.8 S: 0.3 / 0.8	ST: 1.1 / 3.3 TL: 0.6 / 1.4 DI: 4.1 / 5.3	ST: 1.1 / 3.3 TL: 0.6 / 1.4 DI: 4.1 / 5.3	ST: 1.1 / 3.3 TL: 0.6 / 1.4 DI: 4.1 / 5.3	ST: 1.1 / 3.3 TL: 0.6 / 1.4 DI: 4.1 / 5.3	ST: 1.1 / 3.3 TL: 0.6 / 1.4 DI: 4.1 / 5.3	2.3 / 5.1	2.3 / 5.1
389.1 / 104/25	199.8 / 40/25	199.8 / 40/25	199.8 / 40/25	199.8 / 40/25	149.1 / 104/25	275.4 / 104/25	275.4 / 104/25	275.4 / 104/25	275.4 / 104/25	149.1 / 104/25	149.1 / 104/25
•	•	•	•	•	•	•	•	•	•	•	•
2*	2*	2*	2*	2*	2*	2*	2*	2*	2*	2*	2*
0	0	0	0	0	0	0	0	0	0	0	0
•	•	•	•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•	•	•	•
30	6	6	6	6	4 / 12 / 4	4 / 12 / 4	4 / 12 / 4	4 / 12 / 4	4 / 12 / 4	12	12
ST: 305 / 330 TL: 40 / 60	155 / 74	155 / 74	155 / 74	155 / 74	ST: 82 / 118 TL: 45 / 50 DI: 304 / 190	ST: 82 / 118 TL: 45 / 50 DI: 304 / 190	ST: 82 / 118 TL: 45 / 50 DI: 304 / 190	ST: 82 / 118 TL: 45 / 50 DI: 304 / 190	ST: 82 / 118 TL: 45 / 50 DI: 304 / 190	171 / 183	171 / 183
12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24
•	•	•	•	•	•	•	•	•	•	•	•
30	84	84	84	84	35	45	45	45	45	35	35
2SB 013 399-04	2SB 013 343-21	2SB 013 343-22	2SB 013 343-23	2SB 013 343-24	2SD 013 341-01	2SD013 342-11	2SD 013 342-12	2SD 013 342-13	2SD 013 342-14	2BA 013 330-02	2BA 013 330-00
Integrated 3-pin AMP SS	Integrated 3-pin AMP SS	Integrated 3-pin AMP SS	Integrated 3-pin AMP SS	Integrated 3-pin AMP SS	Integrated 4-pin AMP SS	Integrated 4-pin AMP SS	Integrated 4-pin AMP SS	Integrated 4-pin AMP SS	Integrated 4-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS

ST = stop light, TL = tail light, DI = direction indicator

Note: The Shapeline direction indicators (for front and rear), tail-stop lamps and tail-stop-direction indicator lamps are not approved for the vehicle class M1 with < 3.5 t.

											
	Direction indicator amber rear LH hor.	Direction indicator amber rear RH hor.	Direction indicator amber rear LH vert.	Direction indicator amber rear RH vert.	Direction indicator clear rear LH hor.	Direction indicator clear rear RH hor.	Direction indicator clear rear LH vert.	Direction indicator clear rear RH vert.	Direction indicator Wing rear LH hor.	Direction indicator Wing rear RH hor.	Direction indicator Wing rear LH hor. wiping R → L
Design	Style	Style	Style	Style	Style	Style	Style	Style	Style	Style	Style
Homologation	ECE	ECE	ECE	ECE	ECE	ECE	ECE	ECE	ECE	ECE	ECE
Connectors and wiring	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS
Device number (Please add packaging index as the last number - 1 Individual packaging or - 7 Multiple-item packaging)	2BA 013 331-05	2BA 013 331-06	2BA 013 331-07	2BA 013 331-08	2BA 013 331-01	2BA 013 331-02	2BA 013 331-03	2BA 013 331-04	2BA 013 333-01	2BA 013 333-02	2BA 013 333-05
Minimum order quantity for packaging index 7	45	45	45	45	45	45	45	45	30	30	30
Voltage range: 9V – 16V	•	•	•	•	•	•	•	•	•	•	•
Voltage range: 18V – 32V	•	•	•	•	•	•	•	•	•	•	•
Nominal voltage [V]	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24
Current flow at 13.5V/28V [mA]	171 / 183	171 / 183	171 / 183	171 / 183	171 / 183	171 / 183	171 / 183	171 / 183	285 / 315	285 / 315	285 / 315
Number of LEDs	12	12	12	12	12	12	12	12	30	30	30
Power consumption at 13.5V/28V [W]	2,3 / 5,1	2,3 / 5,1	2,3 / 5,1	2,3 / 5,1	2,3 / 5,1	2,3 / 5,1	2,3 / 5,1	2,3 / 5,1	3,9 / 8	3,9 / 8	3,9 / 8
Dimensions (length / width / height in mm)	275,4/104/25	275,4/104/25	275,4/104/25	275,4/104/25	275,4/104/25	275,4/104/25	275,4/104/25	275,4/104/25	389,1/104/25	389,1/104/25	389,1/104/25
Operating temp.: -40 – +60°C	•	•	•	•	•	•	•	•	•	•	•
Mounting system (1= tape; 2= screw; 3= snap-ball-head bolt)*	2*	2*	2*	2*	2*	2*	2*	2*	2*	2*	2*
Mounting tolerance (+/- angle [°])	0	0	0	0	0	0	0	0	6	6	6
HELLA specification HN67101 class 6.3 + 7.2	•	•	•	•	•	•	•	•	•	•	•
Polarity reversal protection	•	•	•	•	•	•	•	•	•	•	•
Failure protection: current detection, 1 LED off = all off											
Failure protection ISO13207	•	•	•	•	•	•	•	•	•	•	•
Integrated short-circuit protection	•	•	•	•	•	•	•	•	•	•	•

* Other fastening options available upon request

Note: The Shapeline direction indicators (for front and rear), tail-stop lamps and tail-stop-direction indicator lamps are not approved for the vehicle class M1 with < 3.5 t.

											
Direction indicator Wing rear RH hor. wiping L → R	Direction indicator Wing rear LH hor. wiping R → L	Direction indicator Wing rear RH hor. wiping L → R	Direction indicator Wing rear LH vert.	Direction indicator Wing rear RH vert.	Direction indicator Slim rear LH hor.	Direction indicator Slim rear RH hor.	Direction indicator Slim rear LH hor. wiping	Direction indicator Slim rear RH hor. wiping	Direction indicator Slim rear LH vert.	Direction indicator Slim rear RH vert.	Reverse lamp
Style	Style	Style	Style	Style	Style	Style	Style	Style	Style	Style	Tech
ECE	ECE	ECE	ECE	ECE	ECE	ECE	ECE	ECE	ECE	ECE	ECE/SAE
Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 3-pin AMP SS
2BA 013 333-06	2BA 013 333-07	2BA 013 333-08	2BA 013 333-03	2BA 013 333-04	2BA 013 332-03	2BA 013 332-04	2BA 013 332-01	2BA 013 332-02	2BA 013 332-05	2BA 013 332-06	2ZR 013 344-10
30	30	30	30	30	84	84	84	84	84	84	35
•	•	•	•	•	•	•	•	•	•	•	•
12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24
285 / 315	285 / 315	285 / 315	285 / 315	285 / 315	130 / 90	130 / 90	130 / 90	130 / 90	130 / 90	130 / 90	230 / 130
30	30	30	30	30	6	6	6	6	6	6	4
3.9 / 8	3.9 / 8	3.9 / 8	3.9 / 8	3.9 / 8	1.8 / 2.5	1.8 / 2.5	1.8 / 2.5	1.8 / 2.5	1.8 / 2.5	1.8 / 2.5	3.1 / 3.6
389.1/104/25	389.1/104/25	389.1/104/25	389.1/104/25	389.1/104/25	199.8/40/25	199.8/40/25	199.8/40/25	199.8/40/25	199.8/40/25	199.8/40/25	149.1/104/25
•	•	•	•	•	•	•	•	•	•	•	•
2*	2*	2*	2*	2*	1*	1*	1*	1*	1*	1*	2*
6	6	6	0	0	6	6	6	6	0	0	0
•	•	•	•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•	•	•	•

Note: The Shapeline direction indicators (for front and rear), tail-stop lamps and tail-stop-direction indicator lamps are not approved for the vehicle class M1 with < 3.5 t.

											
	Reverse lamp LH hor.	Reverse lamp RH hor.	Reverse lamp LH vert.	Reverse lamp RH hor.	Reverse lamp Slim LH hor. (only with 2 modules)	Reverse lamp Slim RH hor. (only with 2 modules)	Reverse lamp Slim LH diag. (only with 2 modules)	Reverse lamp Slim RH diag. (only with 2 modules)	Reverse lamp Slim LH vert. (only with 2 modules)	Reverse lamp Slim RH vert. (only with 2 modules)	Rear fog lamp
Design	Style	Style	Style	Style	Style	Style	Style	Style	Style	Style	Tech
Homologation	ECE/SAE	ECE/SAE	ECE/SAE	ECE/SAE	ECE/SAE	ECE/SAE	ECE/SAE	ECE/SAE	ECE/SAE	ECE/SAE	ECE/SAE
Connectors and wiring	Integrated 3-pin AMP SS (with 2 pin function)	Integrated 3-pin AMP SS (with 2 pin function)	Integrated 3-pin AMP SS (with 2 pin function)	Integrated 3-pin AMP SS (with 2 pin function)	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 3-pin AMP SS
Device number (Please add packaging index as the last number -1 Individual packaging or -7 Multiple-item packaging)	2ZR 013 345-11	2ZR 013 345-12	2ZR 013 345-13	2ZR 013 345-14	2ZR 013 401-01	2ZR 013 401-02	2ZR 013 401-05	2ZR 013 401-06	2ZR 013 401-03	2ZR 013 401-04	2NE 013 344-00
Minimum order quantity for packaging index 7	45	45	45	45	84	84	84	84	84	84	35
Voltage range: 9V – 16V	•	•	•	•	•	•	•	•	•	•	•
Voltage range: 18V – 32V	•	•	•	•	•	•	•	•	•	•	•
Nominal voltage [V]	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24
Current flow at 13.5V/28V [mA]	230 / 130	230 / 130	230 / 130	230 / 130	243 / 117	243 / 117	243 / 117	243 / 117	243 / 117	243 / 117	171 / 100
Number of LEDs	4	4	4	4	6	6	6	6	6	6	12
Power consumption at 13.5V/28V [W]	3,1 / 3,6	3,1 / 3,6	3,1 / 3,6	3,1 / 3,6	max. 2.9	max. 2.9	max. 2.9	max. 2.9	max. 2.9	max. 2.9	2.3 / 2.8
Dimensions (length / width / height in mm)	275,4/104/25	275,4/104/25	275,4/104/25	275,4/104/25	199,8/40/25	199,8/40/25	199,8/40/25	199,8/40/25	199,8/40/25	199,8/40/25	149,1/104/25
Operating temp.: -40 – +60°C	•	•	•	•	•	•	•	•	•	•	•
Mounting system (1= tape; 2= screw; 3= snap-ball-head bolt)*	2*	2*	2*	2*	1*	1*	1*	1*	1*	1*	2*
Mounting tolerance (+/- angle [°])	0	0	0	0	6	6	0	0	0	0	0
HELLA specification HN67101 class 6.3 + 7.2	•	•	•	•	•	•	•	•	•	•	•
Polarity reversal protection	•	•	•	•	•	•	•	•	•	•	•
Failure protection: current detection, 1 LED off = all off					•	•	•	•	•	•	
Failure protection ISO13207											
Integrated short-circuit protection	•	•	•	•	•	•	•	•	•	•	•

* Other fastening options available upon request

[illegible]

•	•	•	•	0	2*	•	149.1/104/25	RFL: 2.3 / 2.8 RL: 3.1 / 3.6	12/ 4	RFL: 171 / 100 RL: 230 / 130	12/24	•	•	35	2NR 013 344-20	Integrated 3-pin AMP SS
•	•	•	•	0	2*	•	275.4/104/25	2.3 / 2.8	12	171 / 100	12/24	•	•	45	2NE 013 345-01	Integrated 3-pin AMP SS (mit 2 Pin-Funktion)
•	•	•	•	0	2*	•	275.4/104/25	2.3 / 2.8	12	171 / 100	12/24	•	•	45	2NE 013 345-02	Integrated 3-pin AMP SS (with 2 pin function)
•	•	•	•	0	2*	•	275.4/104/25	2.3 / 2.8	12	171 / 100	12/24	•	•	45	2NE 013 345-03	Integrated 3-pin AMP SS (with 2 pin function)
•	•	•	•	0	2*	•	275.4/104/25	2.3 / 2.8	12	171 / 100	12/24	•	•	45	2NE 013 345-04	Integrated 3-pin AMP SS (with 2 pin function)
•	•	•	•	0	2*	•	275.4/104/25	RFL: 2.3 / 2.8 RL: 3.1 / 3.6	12/ 4	RFL: 171 / 100 RL: 230 / 130	12/24	•	•	45	2NR 013 345-21	Integrated 3-pin AMP SS
•	•	•	•	0	2*	•	275.4/104/25	RFL: 2.3 / 2.8 RL: 3.1 / 3.6	12/ 4	RFL: 171 / 100 RL: 230 / 130	12/24	•	•	45	2NR 013 345-22	Integrated 3-pin AMP SS
•	•	•	•	0	2*	•	275.4/104/25	RFL: 2.3 / 2.8 RL: 3.1 / 3.6	12/ 4	RFL: 171 / 100 RL: 230 / 130	12/24	•	•	45	2NR 013 345-23	Integrated 3-pin AMP SS
•	•	•	•	0	2*	•	275.4/104/25	RFL: 2.3 / 2.8 RL: 3.1 / 3.6	12/ 4	RFL: 171 / 100 RL: 230 / 130	12/24	•	•	45	2NR 013 345-24	Integrated 3-pin AMP SS
•	•	•	•	6	1*	•	199.8/40/25	max.1.9	6	155 / 74	12/24	•	•	84	2NE 013 343-01	Integrated 2-pin AMP SS
•	•	•	•	6	1*	•	199.8/40/25	max.1.9	6	155 / 74	12/24	•	•	84	2NE 013 343-02	Integrated 2-pin AMP SS
•	•	•	•	0	1*	•	199.8/40/25	max.1.9	6	155 / 74	12/24	•	•	84	2NE 013 343-05	Integrated 2-pin AMP SS

RFL = Rear fog light, RL = Reverse light

												
	Rear fog lamp Slim RH diag.	Rear fog lamp Slim LH vert.	Rear fog lamp Slim RH vert.	Reflex reflector rear	Reflex reflector Wing rear LH	Reflex reflector Wing rear RH	Reflex reflector rear LH	Reflex reflector rear RH	Warning lamp amber LH	Warning lamp amber RH	Warning lamp amber LH	Warning lamp amber RH
Design	Style	Style	Style	Tech	Style	Style	Style	Style	Style	Style	Style	Style
Homologation	ECE	ECE	ECE	ECE/SAE	ECE/SAE	ECE/SAE	ECE/SAE	ECE/SAE	SAE	SAE	SAE	SAE
Connectors and wiring	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS						Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS	Integrated 2-pin AMP SS
Device number (Please add packaging index as the last number -1 Individual packaging or -7 Multiple-item packaging)	2NE 013 343-06	2NE 013 343-03	2NE 013 343-04	8RA 013 403-00	8RA 013 402-01	8RA 013 402-02	8RA 013 347-05	8RA 013 347-06	2XW 013 493-01	2XW 013 493-02	2XW 013 345-29	2XW 013 345-30
Minimum order quantity for packaging index 7	84	84	84	299	30	30	240	240	30	30	180	180
Voltage range: 9V – 16V	•	•	•						•	•	•	•
Voltage range: 18V – 32V	•	•	•						•	•	•	•
Nominal voltage [V]	12/24	12/24	12/24								12/24	12/24
Current flow at 13.5V/28V [mA]	155 / 74	155 / 74	155 / 74						407 / 197	407 / 197	518 / 273	518 / 273
Number of LEDs	6	6	6								12	12
Power consumption at 13.5V/28V [W]	max. 1,9	max. 1,9	max. 1,9						max. 5,5	max. 5,5	7,2 / 7,6	7,2 / 7,6
Dimensions (length / width / height in mm)	199,8 / 40/25	199,8 / 40/25	199,8 / 40/25	113 / 40/12	389,1 / 104/25	389,1 / 104/25	163,5 / 40/12	163,5 / 40/12	389,1 / 104/25	389,1 / 104/25	275,4 / 104/25	275,4 / 104/25
Operating temp.: -40 – +60°C	•	•	•	•	•	•	•	•	•	•	•	•
Mounting system (1= tape; 2= screw; 3= snap-ball-head bolt)*	1*	1*	1*	1	2*	2*	1	1	2*	2*	2*	2*
Mounting tolerance (+/- angle [°])	0	0	0	0	6	6	6	6	0	0	0	0
HELLA specification HN67101 class 6.3 + 7.2	•	•	•	•	•	•	•	•	•	•	•	•
Polarity reversal protection	•	•	•								•	•
Failure protection: current detection, 1 LED off = all off	•	•	•								•	•
Failure protection ISO13207												
Integrated short-circuit protection	•	•	•								•	•

* Other fastening options upon request

CONNECTOR OVERVIEW

The tables on the previous pages show you which connectors and which wiring belong to which Shapeline product. The following shows you what the different connector types look like.



6.3 mm receptacle



Open ends



QL - Quick Link



Amphenol



Integrated AMP SUPERSEAL



AMP SUPERSEAL



EC - EasyConn straight/
angled

ASSEMBLY INSTRUCTIONS FOR SIDE MARKER LAMPS



**Specifically
for trailers!**

We offer you special installation angles for the simple assembly of the Shapeline side marker lamps on the trailer chassis. The installation angles are available either individually or in combination with a side marker lamp, and are compatible with screw ball pin or snapping ball pin fixing systems.



Angle bracket
for screw fixing system



Angle bracket
for ball pin fixing system



Side marker lamp including angle bracket
for screw fixing system

OVERVIEW OF SIDE MARKER LAMPS INCLUDING INSTALLATION ANGLES:

	Side marker lamp with reflex reflector	Side marker lamp with reflex reflector	Side marker lamp with reflex reflector	Side marker lamp with reflex reflector	Installation angle	Installation angle
	Amber hor.	Amber hor.	Amber hor.	Amber hor.	for Shapeline groups of side marker lamp with reflex reflector 013 300 (Tech), 013 302 (Tech), 013 305 (Style), 013 306 (Style)	for Shapeline groups of side marker lamp with reflex reflector 013 300 (Tech), 013 302 (Tech), 013 305 (Style), 013 306 (Style)
	Including installation angle	Including installation angle	Including installation angle	Including installation angle		
Design	Tech	Tech	Tech	Tech		
Homologation	ECE SM1 / SAE	ECE SM1 / SAE	ECE SM1 / SAE	ECE SM1 / SAE		
Connectors and wiring	EC straight 1300 mm	QL 1300 mm	6.3 mm receptacles 2100 mm	Open ends 1500 mm		
Part number	2PS 013 300-717	2PS 013 300-727	2PS 013 300-737	2PS 013 300-747	8HG 160 409-012	8HG 160 409-022
Fixing system	Screw fixing for installation angle	Screw fixing for installation angle	Screw fixing for installation angle	Screw fixing for installation angle	M5 screw fixing for the light	Ball pin fixing for the light

Other combinations of side marker lamp with reflex reflector/wing are available upon request. More detailed information on the side marker lamps can be found on pages 22 - 25.



SHAPELINE
DESIGN YOUR LIGHT

www.hella.com/shapeline

HELLA GmbH & Co. KGaA

Rixbecker Straße 75

59552 Lippstadt, Germany

Tel.: +49 2941 38-0

Fax: +49 2941 38-7133

Internet: www.hella.com

© HELLA GmbH & Co. KGaA, Lippstadt
J01721/02.21
Subject to technical and price modifications.

www.hella.com/shapeline